OMGA®
WOOD be nice.



T50 350
T53 370

Precision mitre saws

OMGA®
WOOD be nice.

T50 350
T53 370:
ABSOLUTE STRENGTH



T50 **350**



T53 **370**




Precision mitre saws with rotating table and selfcentering locking for the main angles 90°, 45°, 30°, 22°,30', 15°, 10° right and left; manual locking for all the other intermediate angles, with reading on the scale. The main characteristics of these mitre saws: structure in cast iron, motor of 2.2 kW with transmission by belt and blade of ø 350 mm. (ø 370 mm. on the model T 53), they ensure an absolute strength and a large cutting capacity.

The model **T53 370** differentiates by the model **T50 350** for the possibility to tilt the head on the vertical axis up to 45°, arriving therefore to perform compound angle cuts to any possible angle. Both models can be equipped with a wide accessories range.


The version "OP" has been created as a separate model, including the machine in "CE" version with oilpneumatic downstroke, with two hand control for the downstroke of the head, two pneumatic horizontal clamps in cycle with the cutting action, cabinet, side extensions.

TYPES OF CUT

T50 **350**




T53 **370**



OPTIONAL (T50 350 - T53 370)




Dust collecting cabinet



Double horizontal clamps:
45° mechanical with foot-pedal
45° pneumatic with foot-pedal
90° pneumatic with lever



Quick swivelling with pneum. locking



Pneumatic horizontal clamp
Pneumatic vertical clamp



Oil-pneumatic feed of head




Set of scaled tables - Support to join scaled tables to cabinet - Nylon flip-over stop - Plexi flip-over stop

www.apvd.it


OMGA®
WOOD be nice.

		T50 **350**	T53 **370**
Cross cut capacity	90°	6-3/4"	6-3/4"
Cross cut capacity with head at	45°	4 1.8"	4 1.8"
Max. depth of cut with head at	45°	-	2"
Max. depth	90°	4-5/16"	4-5/16"
Motor power	HP	3	4
Saw bore		1'	1'
Saw diameter		14"	14"
Arbor speed	RPM	3400	3400
Dust chute		3-1/8"	3-1/8"
Mitre positive stops		90°- 45°- 30°- 22-1/2°- 15°- 10°	90°- 45°- 30°- 22-1/2°- 15°- 10°
Table size		23-5/8"x17-1/8"x5-3/16"	23-5/8"x17-1/8"x5-3/16"
Crated dimensions		26"x 25"x 30"	30"x32"x30"
Approx. shipping weight	lbs.	269	330


SOME EXAMPLES OF COMPOSITION WITH OPTIONAL



Omga Stop and Table extension



Roller tables, Infeed/Outfeed



Omga Stop and Table extension

OMGA Industries, Inc.
3705 William Richardson Drive
South Bend, IN 46628 USA
Tel.: +1 (574) 243-0120
Fax: +1 (574) 243-0216
Toll Free: 1-800-233-OMGA (6642)
info@omgainc.com
www.omgainc.com

2900204546.08 - **USA**

The information and data provided may be subject to modification without prior notice.